

A9A15310

DIN socket iPC - 2P+E - 16A - 250VAC - KEMA VDE 0620 - german std



Main

Range of product	Acti 9
Product or component type	Socket
Device short name	IPC
Poles description	2P + E
Outlet standard	German

Complementary

[In] rated current	16 A
[Ue] rated operational voltage	250 V AC 50/60 Hz
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
9 mm pitches	5
Height	84 mm
Width	45 mm
Depth	63 mm
Product weight	0.098 kg
Colour	White
Connections - terminals	Tunnel type terminal 1 cable(s) flexible 6 mm ² Tunnel type terminal 1 cable(s) rigid 10 mm ²
Wire stripping length	13 mm
Tightening torque	1.2 N.m

Environment

Standards	VDE 0620
IP degree of protection	IP20 conforming to IEC 60529 IP40 conforming to IEC 60529
IK degree of protection	IK03
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % (55 °C)

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1312 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.